

FREE
HOSE
PIPE



5 STAR ENERGY RATING

STORAGE WATER HEATER VERTICAL

Available in **06,10,15 & 25 Ltr**

*True Quality.
Trusted Service.
Since 1960*

PRODUCT SPECIFICATIONS

Product Description	Ultra Vertical Manual 06LTR, 10LTR, 15LTR & 25LTR		
Rated Wattage	2 kW		
Tank Volume (L)	06/10/15/25		
High Pressure Rating	8 Bar		
Outer Body Material	ABS		
Multi-Function Safety Valve	Yes		
Insulation, Density	PUF		
Inner Container Material	Steel with Glass lined		
Heating element type	Incoloy with Glass coated heating element		
Anode	Yes		
Voltage /Frequency	230 V/50 Hz		
Shape	Cylindrical		
Warranty	5 Years on Tank 2 Years on Heating Element 2 Years on Other Parts		
Product Dimension (in mm)		W	H
	06 L	285	375
	10 L	285	475
	15 L	380	440
	25 L	380	580



Key Features



Introducing the new Essco Storage Water Heater range that comes with **Glasslined Tank** that counter scale, sediment, residue build up on the surface of the water heater tank over time due to the hard water. The Glasslined Tank prevent corrosion when it is in contact with warm water. This increases the longevity of the appliance enhancing your bathing experience.



CFC free high density Polyurathane insulation keeps the water hot and prevents heat loss for a long time. It reduces energy consumption and provides high energy efficiency



Incoloy Heating Element

Incoloy Heating Element offers superior heating performance with resistance to carbonization and oxidation at high temperature . It also resist corrosion against hard water resulting extended lif span of heating element.



Magnesium anode

The tank has a magnesium anode rod that is designed to protect the tank from corrosive element. It works as a sacrificial anode keep the tank rust proof and ensure a longer life



8 bar high working pressure

Suitable for high rise buildings and pressure pump applications. Pressure withstanding capacity up to 8 bar for Essco Storage Electric Water Heater(Ground+18 Floors/ 270 Feet) and pressure withstanding up to 6.5 bar For Essco Instant Electric Water Heater (Ground+14 Floors/ 210 Feet



Multi function safety valve

It prevents malfunction during abnormal conditions like high pressure etc. There are four functions of the safety valve - Pressure release, Vacuum release, non-return and draining. The MFSV prevents pressure to increase beyond 8 bar.

**True Quality.
Trusted Service.
Since 1960**